


Lot 12	
LTF = 691.98	LOWEST TOP OF FOOTING ELEVATION (TYP 0.70m ABOVE SAN @ P/L)
SAN = 691.06*	SANITARY SEWER INVERT ELEVATION AT PROPERTY LINE
TF-BC = 692.74	TOP OF FOOTING ELEVATION ABOVE WHICH A BEARING CERTIFICATE IS REQUIRED
TF-DF = 692.24	TOP OF FOOTING ELEVATION ABOVE WHICH A DEEP FILL FOUNDATION IS REQUIRED
MBOE = 692.59	MINIMUM BUILDING OPENING ELEVATION (0.30m ABOVE HIGH WATER LEVEL)



**NOTES:**

- CURB STOP LOCATION IS APPROX. 0.30m FROM FRONT OF PROPERTY LINE INTO THE ROAD ROW
  - PIGTAIL LOCATION FOR LOT SERVICES ARE APPROX. 5.0m FROM CURB STOP INTO THE LOT
  - ELECTRIC SERVICE IS LOCATED 1.2m INTO PROPERTY FROM FRONT PROPERTY LINE.
  - GAS SERVICE IS LOCATED 2.4m INTO PROPERTY FROM PROPERTY LINE
  - ALL FOUNDATION CONCRETE IS TO BE TYPE 50 (SULPHATE RESISTANT) CEMENT WITH A 56-DAY COMPRESSIVE STRENGTH OF 32 MPa AND WITH A MINIMUM WATER TO CEMENTING MATERIAL RATIO OF 0.45. THE ADDITION OF +5% AIR ENTRAINMENT IS ALSO RECOMMENDED FOR CONCRETE EXPOSED TO FREEZE-THAW CONDITIONS.
  - REFER TO REGISTERED LEGAL PLAN FOR LEGAL DIMENSIONS, BEARINGS AND PIN LOCATIONS
  - INFORMATION BASED ON SUBDIVISION DESIGN PROVIDED BY SCHEFFER ANDREW LTD.
- \* - DENOTES CORRECTED ELEVATION (SEPT 27, 2019)



# LANDMARK PROPERTIES

## HERON CROSSING - PHASE 1 BLK 1, LOT 12



- (A) LOT GRADING TYPE A  
BACK TO FRONT DRAINAGE 2-3% OVERALL SLOPE
- (B) LOT GRADING TYPE B  
BACK TO FRONT DRAINAGE 3-6% OVERALL SLOPE
- (D) LOT GRADING TYPE D  
STANDARD SPLIT DRAINAGE
- (S) LOT GRADING TYPE S  
SPLIT DRAINAGE, POSSIBLE WALKOUT BASEMENT  
(CAREFUL GRADING REQUIRED)
- (W) LOT GRADING TYPE W  
SPLIT DRAINAGE, POSSIBLE WALKOUT BASEMENT  
(CAREFUL GRADING REQUIRED)

\* LOTS WITH FILL IN EXCESS OF 1.2m: ANY LOT THAT HAS ANY PART OR PORTION OF ITS FOUNDATION ON FILL WILL REQUIRE A BEARING CERTIFICATE

— P — POWER UTILITY  
— G — GAS UTILITY